## Product Features:

المنظار USB للماء كاميرا 5MM
2M / 5M / 7M / 10M / 20M،
ضوء LEDالكاميرا، 6CMOS 6 / 1
المنتجات الجديدة التصميم الجديد.
ماء: IP67

صحيح التوصيل وأمبير. لعب بدون تثبيت برنامج التشغيل دون نظام XP
يمكن حفظ الفيديو، وتأخذ الصورة، ووضع بكسل فيديو / الحجم / إطار / CD، عند إدراج sytem XP تثبيتها تلقائيا البرنامج أعلاه النمط، الخ
امدادات الطاقة: DC 5V / 0.1A

| البنود وظيفة | المواصفات الوصف |
|---|---|
| كاميرا | 1/6 "COMS VGA |
| بكسل | 640 X 480 |
| قرار | 640x480،352X288،320X240،176X144،160X120 |
| القرار Captuer | X480تصل إلى 640 |
| الصمام | 4 الضوء الساطع LED الأبيض |
| سطوع | السيارات |
| السيطرة يتعرض | السيارات |
| F / NO | 2.8 |
| كاميرا الاسكان بقطر | Φ7.00 مم |
| زاوية واسعة نظرا البصرية | 62 ° |
| التبديل LED | قابل للتعديل التبديل خفة |
| الاتصال عن بعد | 6CM-infinate |

**خدماتنا**

1. أعلى جودة وأفضل سعر
2. لا يقل عن 3 مرات اختبار قبل التسليم
3. 24 أشهر الضمان
4. أسرع الشحن
5. CE، بنفايات وافقت
6. محاكمة النظام ورحب
7. شروط الدفع المرنة

## Product Pictures:

10M

6 LEDS
5.5mm

**انظر أدناه للحصول على مزيد من اختيار النموذج:**

## 7mm 6-LED USB Endoscope Camera

| Item | Picture | Packing | Specification |
|---|---|---|---|
| SE-702M<br>SE-705M<br>SE-707M<br>SE-710M<br>SE-715M<br>SE-720M | | | Camera 1/6" VGA COMS<br>Pixel VGA 300K<br>**Resolution 640x480**, F/NO 2.8<br>LED 6 White LED bright light,<br>Camera housing diameter Φ7mm<br>Wide visual view angle 62°<br>LED swith Adjustable lightness switch<br>Focal Distance 6CM-infinite<br>I/O Interface USB 2.0<br>Packing details: endoscope camera, CD, manual.<br>G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g |

## 5.5mm 6-LED USB Endoscope Camera

| Item | Picture | Packing | Specification |
|---|---|---|---|
| E-USB2M<br>E-USB5M<br>E-USB7M<br>E-USB10M<br>E-USB15M<br>E-USB20M | | | Camera 1/6" VGA COMS<br>Pixel VGA 300K<br>**Resolution 640x480**, F/NO 2.8<br>LED 6 White LED bright light,<br>Camera housing diameter **Φ5.5mm**<br>Wide visual view angle 62°<br>LED swith Adjustable lightness switch<br>Focal Distance 6CM-infinite<br>I/O Interface USB 2.0<br>Packing details: endoscope camera,<br>G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g |

## 14.5mm 4-LED USB Endoscope Camera

| Item | Picture | Packing | Specification |
|---|---|---|---|
| EN-5M<br>EN-10M<br>EN-15M<br>EN-20M | | | Camera 1/6" VGA COMS<br>Pixel VGA 300K<br>Resolution 640x480, F/NO 2.8<br>LED 6 White LED bright light,<br>Camera housing diameter Φ14.5mm<br>Wide visual view angle 62°<br>LED swith Adjustable lightness switch<br>Focal Distance 6CM-infinite<br>I/O Interface USB 2.0<br>Packing details: endoscope camera, CD, manual.<br>G.W: 5M:230g 10M:410g 15M:560g 20M:710g |

## 10mm 4-LED Endoscope Camera

| Item | Picture | Packing | Specification |
|---|---|---|---|
| USB-2M<br>USB-5M<br>USB-7M<br>USB-10M<br>USB-15M<br>USB-20M | <br> | <br> | Camera 1/6" VGA COMS<br>Pixel VGA 300K<br>Resolution 640x480, F/NO 2.8<br>LED 4 White LED bright light,<br>Camera housing diameter Φ10mm<br>Wide visual view angle 62°<br>LED swith Adjustable lightness switch<br>Focal Distance 6CM-infinite<br>I/O Interface USB 2.0<br>Packing details: endoscope camera, CD, manual.<br>G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g |

## Approval Certification:

CQC

QUALITY MANAGEMENT SYSTEM

CERTIFICATE

Certificate No.: [illegible]

We hereby certify that:

Zhejiang New-epoch Communication Facility Co., Ltd

Selectech Electronics co.,Ltd

[illegible]

By reason of its

Quality Management System

has been awarded this certificate for compliance with the standard

ISO9001: 2008

GB/T 19001-2008

The Quality Management System Applies to the following area:

[illegible]

Exclusive Design and Development Requirement

Certified since: Jan. 12, 2004 Valid from: Feb. 06, 2018 Valid until: Feb. 06, 2019

[illegible]

Signed by: [illegible]

CHINA QUALITY CERTIFICATION CENTRE

[illegible]

Union Safety Certification Service

*EC Declaration of Conformity*

No. [illegible]

The following products have been tested by us with the listed standards and found in compliance with the European Community Low Voltage Directive (LVD) 2006/95/EC and 93/96/EEC.

Assessment of compliance of the product with the requirements was based on the following standards:

EN60335-1:2012

EN62233:2008

| | |
|---|---|
| Applicant | : Selectech Electronics co.,Ltd |
| Address | : No.56, Renhe Road, Renhe Town, Baiyun District, Guangzhou, China |
| Product | : Humidity & temp Sensor |
| Model No. | : AM2301/AM2302/AM2303/AM2305/AM2306/AM2321 |
| Input Ratings | : 3.0-6.5V |
| Ref. Test Report | : 16002481 001 |

CE

Manager

Date: [illegible]

[illegible]

Union Safety Certification Service

Address: [illegible]

Union Safety Certification Service

*Declaration of Compliance*

No.: [illegible]

| | |
|---|---|
| Applicant | : Selectech Electronics co.,Ltd |
| Address | : No.56, Renhe Road, Renhe Town, Baiyun District, Guangzhou, China |
| Product | : Humidity & temp Sensor |
| Model No. | : AM2301/AM2302/AM2303/AM2305/AM2306/AM2321 |
| Input Ratings | : 3.0-6.5V |
| Ref. Test Report | : 16002483 001 |

This is to certify that , on the basis of the tests undertaken as report no.: 16002483 001, use the submitted sample of the above item complies with:

2011/65/EU

2006/9/16/EC

**RoHS**

Signed and on behalf of

Union safety Certification Service

[illegible]

Date of issue: [illegible]

Union Safety Certification Service

[illegible]

## Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

1.Established in 2005, about 10 years of history;

2.Own main factories, supply diversification products and One stop service

3.Certificates of ISO9001, UL, CE, EMC,CQC,RoHS,Reach,etc.

4.Six years Gold member in Alibaba, Aliexpress etc

5.Production capability more than 100 thousands pcs/ month;

6.Monthly export more than 50 times delivery;

7.Exported to more than 20 countries and regions;

8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!