



### Product Features:

المنظار USB للماء كاميرا 5MM  
 2M / 5M / 7M / 10M / 20M,  
 ضوء LED الكاميرا، 6 / 1 CMOS  
 المنتجات الجديدة التصميم الجديد.  
 ماء: IP67

XP صحيح التوصيل وأمبير. لعب بدون تثبيت برنامج التشغيل دون نظام  
 يمكن حفظ الفيديو، وتأخذ الصورة، ووضع بكسل فيديو / الحجم / إطار / CD، عند إدراج sytem XP تثبيتها تلقائيا البرنامج أعلاه  
 النمط، الخ  
 امدادات الطاقة: DC 5V / 0.1A

البنود وظيفية	المواصفات الوصف
كاميرا	1/6 "COMS VGA
بكسل	640 X 480
قرار	640x480,352X288,320X240,176X144,160X120
القرار Captuer	640X480 تصل إلى
الصمام	الضوء الساطع LED الأبيض 4
سطوع	السيارات
السيطرة يتعرض	السيارات
F / NO	2.8
كاميرا الاسكان بقطر	Φ7.00 مم
زاوية واسعة نظرا البصرية	62 °
LED التبديل	قابل للتعديل التبديل خفة
الاتصال عن بعد	6CM-infinite

### خدماتنا

1. أعلى جودة وأفضل سعر.
2. لا يقل عن 3 مرات اختبار قبل التسليم
3. 24 أشهر الضمان
4. أسرع الشحن
5. بنفايات وافقت، CE.
6. محاكمة النظام
7. شروط الدفع المرنة

### Product Pictures:





**انظر أدناه للحصول على مزيد من اختيار النموذج**

### 7mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K
SE-705M			<b>Resolution 640x480</b> , F/NO 2.8
SE-707M			LED 6 White LED bright light, <b>Camera housing diameter <math>\Phi</math>7mm</b>
SE-710M			Wide visual view angle 62°
SE-715M			LED swith Adjustable lightness switch
SE-720M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g

### 5.5mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
E-USB2M			Camera 1/6" VGA COMS Pixel VGA 300K
E-USB5M			<b>Resolution 640x480</b> , F/NO 2.8
E-USB7M			LED 6 White LED bright light, <b>Camera housing diameter <math>\Phi</math>5.5mm</b>
E-USB10M			Wide visual view angle 62°
E-USB15M			LED swith Adjustable lightness switch
E-USB20M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g

### 14.5mm 4-LED USB Endoscope Camera

Item	Picture	Packing	Specification
EN-5M			Camera 1/6" VGA COMS Pixel VGA 300K
EN-10M			Resolution 640x480, F/NO 2.8
EN-15M			LED 6 White LED bright light, <b>Camera housing diameter <math>\Phi</math>14.5mm</b>
EN-20M			Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 5M:230g 10M:410g 15M:560g 20M:710g

### 10mm 4-LED Endoscope Camera

Item	Picture	Packing	Specification
USB-2M			Camera 1/6" VGA COMS Pixel VGA 300K
USB-5M			Resolution 640x480, F/NO 2.8
USB-7M			LED 4 White LED bright light, <b>Camera housing diameter <math>\Phi</math>10mm</b>
USB-10M			Wide visual view angle 62°
USB-15M			LED swith Adjustable lightness switch
USB-20M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g

# Approval Certification:



## Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

- 1.Established in 2005, about 10 years of history;
- 2.Own main factories, supply diversification products and One stop service
- 3.Certificates of ISO9001, UL, CE, EMC,CQC,RoHS,Reach,etc.
- 4.Six years Gold member in Alibaba, Aliexpress etc
- 5.Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!

