



Product Features:

wasserdicht 5mm usb Endoskopkamera
 2M / 5M / 7M / 10M / 20M,
 1 / 6CMOS Kamera, 6LED Licht
 Neue Produkte im neuen Design.
 Wasserdicht: IP67

Echte Plug & amp; Spielen ohne Treiber-Installation unter XP-System
 Automatisch installiert, die Software über den XP system beim Einlegen CD können Video zu speichern,
 nehmen Foto, Video-Einstellung Pixel / Größe / Rahmen / Stil, etc.
 Stromversorgung: DC 5V / 0,1A

Funktionselemente	Spec Beschreibung
Kamera	1/6 "VGA COMS
Pixel	640 x 480
Auflösung	640x480,352X288,320X240,176X144,160X120
Captuer Resolution	Bis zu 640x480
LED	4 weiße LED helles Licht
Helligkeit	Auto
Ausgesetzt Steuer	Auto
F / NO	2.8
Kameragehäusedurchmesser	Φ7.00 mm
Breiter Sichtansichtwinkel	62 & deg;
LED-Schalter	Einstellbare Helligkeit Schalter
Brennweite	6CM-infinite

Unsere Dienstleistungen

1. Top Qualität und besten Preis
2. Mindestens 3 mal testen vor der Auslieferung
3. 24 Monate Herstellergarantie
4. Schneller Versand
5. CER, ROHS genehmigt
6. Probeauftrag wird begrüßt
7. Flexible Zahlungsbedingungen

Product Pictures:



6 LEDs

5.5 mm



Siehe unten für weitere Modellauswahl:

7mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480 , F/NO 2.8 LED 6 White LED bright light, Camera housing diameter Φ7mm Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g
SE-705M			
SE-707M			
SE-710M			
SE-715M			
SE-720M			

5.5mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
E-USB2M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480 , F/NO 2.8 LED 6 White LED bright light, Camera housing diameter Φ5.5mm Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g
E-USB5M			
E-USB7M			
E-USB10M			
E-USB15M			
E-USB20M			

14.5mm 4-LED USB Endoscope Camera

Item	Picture	Packing	Specification
EN-5M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 6 White LED bright light, Camera housing diameter Φ14.5mm Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 5M:230g 10M:410g 15M:560g 20M:710g
EN-10M			
EN-15M			
EN-20M			

10mm 4-LED Endoscope Camera

Item	Picture	Packing	Specification
USB-2M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 4 White LED bright light, Camera housing diameter Φ10mm Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g
USB-5M			
USB-7M			
USB-10M			
USB-15M			
USB-20M			

Approval Certification:



Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

- 1.Established in 2005, about 10 years of history;
- 2.Own main factories, supply diversification products and One stop service
- 3.Certificates of ISO9001, UL, CE, EMC,CQC,RoHS,Reach,etc.
- 4.Six years Gold member in Alibaba, Aliexpress etc
- 5.Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!

