



Product Features:

IP67 medizinischen Endoskoprohr Kamera
 Videos, Fotos zu speichern in Ihrem PC
 Wir sind Originalhersteller
 6LED helle Licht einstellbar

Hauptmerkmale

- * Wasserdicht Draht Endoskop
- * Hohe Entschleißung mit 1/6 CMOS-Kamera
- * 6 LED-niedrige Luxhelligkeitlichter kann besser arbeiten, wenn das Licht ist dunkel
- * XP-System kann Video direkt ohne Installation von Software zu starten, Vista oder Win7 benötigen unsere Software, die in der CD
- * Kann Foto nehmen und speichern Sie sie auf Ihrem PC
- * Kann Video und speichern Sie das Video auf Ihrem PC
- * Wird von Auto, Motor, mechanische, Sanitär-, Klimaanlage und andere Wartungserkennung
- * Assist sehen Sie schwierig ist, an die Position und den Zugang

Verpackung:

1. Optional waterpooof seitigen Linsen x1
2. Feld Farbe x1
3. Benutzer Handbuch x1
4. CD x1
5. Der Draht Nockeneinheit x1

Product Pictures:



With waterpooof side lens





Siehe unten für weitere Modellauswahl:

7mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K
SE-705M			Resolution 640x480 , F/NO 2.8
SE-707M			LED 6 White LED bright light, Camera housing diameter Φ7mm
SE-710M			Wide visual view angle 62°
SE-715M			LED swith Adjustable lightness switch
SE-720M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g

5.5mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
E-USB2M			Camera 1/6" VGA COMS Pixel VGA 300K
E-USB5M			Resolution 640x480 , F/NO 2.8
E-USB7M			LED 6 White LED bright light, Camera housing diameter Φ5.5mm
E-USB10M			Wide visual view angle 62°
E-USB15M			LED swith Adjustable lightness switch
E-USB20M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g

14.5mm 4-LED USB Endoscope Camera

Item	Picture	Packing	Specification
EN-5M			Camera 1/6" VGA COMS Pixel VGA 300K
EN-10M			Resolution 640x480, F/NO 2.8
EN-15M			LED 6 White LED bright light, Camera housing diameter Φ14.5mm
EN-20M			Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 5M:230g 10M:410g 15M:560g 20M:710g

10mm 4-LED Endoscope Camera

Item	Picture	Packing	Specification
USB-2M			Camera 1/6" VGA COMS Pixel VGA 300K
USB-5M			Resolution 640x480, F/NO 2.8
USB-7M			LED 4 White LED bright light, Camera housing diameter Φ10mm
USB-10M			Wide visual view angle 62°
USB-15M			LED swith Adjustable lightness switch
USB-20M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g

Approval Certification:



Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

- 1.Established in 2005, about 10 years of history;
- 2.Own main factories, supply diversification products and One stop service
- 3.Certificates of ISO9001, UL, CE, EMC,CQC,RoHS,Reach,etc.
- 4.Six years Gold member in Alibaba, Aliexpress etc
- 5.Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!

