



### Product Features:

5 mm a prueba de agua la cámara endoscopio usb  
 2M / 5M / 7M / 10M / 20M,  
 1 / cámara 6CMOS, luz 6LED  
 Novedades del nuevo diseño.  
 Resistente al agua: IP67

Verdadero Plug & amp; Juega sin la instalación del conductor continuación sistema XP  
 Instala automáticamente el software por encima del Inglés XP al insertar el CD, puede guardar el vídeo,  
 toma la foto, el establecimiento de video píxeles / tamaño / marco / estilo, etc.  
 Fuente de alimentación: DC 5V / 0.1A

Elementos de función	Spec Descripción
Cámara	1/6 "COMS VGA
Pixel	640 X 480
Resolución	640x480,352X288,320X240,176X144,160X120
Resolución Captuer	Hasta 640X480
LED	4 LED blanco luz brillante
Brillo	Auto
Control Expuestos	Auto
F / NO	2.8
Cámara diámetro vivienda	Φ7.00 mm
Amplio ángulo de vista visual	62 °
Interruptor LED	Interruptor ajustable de la ligereza
Distancia focal	-6CM inifate

### Nuestros Servicios

1. de calidad superior y el mejor precio
2. Por lo menos 3 veces a prueba antes de la entrega
3. 24 meses de garantía
4. envío más rápido
5. CE, ROHS aprobados
6. La orden de ensayo es bienvenida
7. Condiciones de pago flexibles

### Product Pictures:





**Ver abajo para más selección del modelo:**

### 7mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K <b>Resolution 640x480</b> , F/NO 2.8 LED 6 White LED bright light, <b>Camera housing diameter Φ7mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g
SE-705M			
SE-707M			
SE-710M			
SE-715M			
SE-720M			

### 5.5mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
E-USB2M			Camera 1/6" VGA COMS Pixel VGA 300K <b>Resolution 640x480</b> , F/NO 2.8 LED 6 White LED bright light, <b>Camera housing diameter Φ5.5mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g
E-USB5M			
E-USB7M			
E-USB10M			
E-USB15M			
E-USB20M			

### 14.5mm 4-LED USB Endoscope Camera

Item	Picture	Packing	Specification
EN-5M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 6 White LED bright light, <b>Camera housing diameter Φ14.5mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 5M:230g 10M:410g 15M:560g 20M:710g
EN-10M			
EN-15M			
EN-20M			

### 10mm 4-LED Endoscope Camera

Item	Picture	Packing	Specification
USB-2M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 4 White LED bright light, <b>Camera housing diameter Φ10mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g
USB-5M			
USB-7M			
USB-10M			
USB-15M			
USB-20M			

# Approval Certification:



## Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

- 1.Established in 2005, about 10 years of history;
- 2.Own main factories, supply diversification products and One stop service
- 3.Certificates of ISO9001, UL, CE, EMC,CQC,RoHS,Reach,etc.
- 4.Six years Gold member in Alibaba, Aliexpress etc
- 5.Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!

