



### Product Features:

IP67 cámara tubo de endoscopio médico  
guardar vídeo, foto en tu PC  
Somos fabricante original de  
6LED luz brillante ajustable

### Características principales

- \* Impermeable endoscopio alambre
- \* Alta resolución con 1/6 cámara CMOS
- \* 6 luces bajas de luminancia lux del LED pueden trabajar mejor cuando la luz es oscuro
- \* Sistema de XP puede ver el video directamente sin instalar software, Vista o Win7 necesitan utilizar nuestro software que en el CD
- \* Puede tomar la foto y guardarlo en su PC
- \* Puede grabar vídeo y guardar el vídeo en el PC
- \* Utilizado por automóvil, motor, mecánica, plomería, aire acondicionado y otros de detección de mantenimiento
- \* Participa examinado es difícil de ver y el acceso a la ubicación

### Embalaje:

1. Olente lado waterpoof pcional x1
2. Caja de color x1
3. Los usuarios x1 Manual
- X1 4. CD
5. La unidad de leva alambre x1

### Product Pictures:



With waterpooof side lens





**Ver abajo para más selección del modelo:**

### 7mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K
SE-705M			<b>Resolution 640x480</b> , F/NO 2.8
SE-707M			LED 6 White LED bright light, <b>Camera housing diameter <math>\Phi</math>7mm</b>
SE-710M			Wide visual view angle 62°
SE-715M			LED swith Adjustable lightness switch
SE-720M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g

### 5.5mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
E-USB2M			Camera 1/6" VGA COMS Pixel VGA 300K
E-USB5M			<b>Resolution 640x480</b> , F/NO 2.8
E-USB7M			LED 6 White LED bright light, <b>Camera housing diameter <math>\Phi</math>5.5mm</b>
E-USB10M			Wide visual view angle 62°
E-USB15M			LED swith Adjustable lightness switch
E-USB20M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g

### 14.5mm 4-LED USB Endoscope Camera

Item	Picture	Packing	Specification
EN-5M			Camera 1/6" VGA COMS Pixel VGA 300K
EN-10M			Resolution 640x480, F/NO 2.8
EN-15M			LED 6 White LED bright light, <b>Camera housing diameter <math>\Phi</math>14.5mm</b>
EN-20M			Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 5M:230g 10M:410g 15M:560g 20M:710g

### 10mm 4-LED Endoscope Camera

Item	Picture	Packing	Specification
USB-2M			Camera 1/6" VGA COMS Pixel VGA 300K
USB-5M			Resolution 640x480, F/NO 2.8
USB-7M			LED 4 White LED bright light, <b>Camera housing diameter <math>\Phi</math>10mm</b>
USB-10M			Wide visual view angle 62°
USB-15M			LED swith Adjustable lightness switch
USB-20M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g

# Approval Certification:



## Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

- 1.Established in 2005, about 10 years of history;
- 2.Own main factories, supply diversification products and One stop service
- 3.Certificates of ISO9001, UL, CE, EMC,CQC,RoHS,Reach,etc.
- 4.Six years Gold member in Alibaba, Aliexpress etc
- 5.Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!

