



Product Features:

5mm étanche caméra usb endoscope
 2M / 5M / 7M / 10M / 20M,
 1 caméra / 6CMOS, la lumière 6LED
 Nouveaux produits nouvelle conception.
 Waterproof: IP67

Vrai Plug & amp; Jouez sans installation de pilote ci-dessous système XP
 Automatiquement installé le logiciel au-dessus du sytem XP lorsque vous insérez le CD, peut sauver vidéo,
 prendre des photos, la mise en pixels vidéo / taille / châssis / le style, etc.
 Alimentation: DC 5V / 0.1A

les éléments de fonction	Spec description
Caméra	1/6 "COMS VGA
Pixel	640 X 480
Résolution	640x480,352X288,320X240,176X144,160X120
Captuer Résolution	Jusqu'à 640X480
LED	4 LED blanche lumière
Luminosité	Auto
Témoin exposé	Auto
F / NO	2.8
diamètre du boîtier de l'appareil photo	Φ7.00 mm
Large angle de vue visuel	62 °
Interrupteur LED	Interrupteur de légèreté réglable
Distance focale	6cm-infinite

Nos Services

1. Haut qualité et le meilleur prix
2. Au moins 3 fois tester avant la livraison
3. la garantie 24 mois
4. Livraison rapide
5. CE, ROHS approuvés
6. Afin de première instance est la bienvenue
7. Conditions de paiement flexibles

Product Pictures:





Voir ci-dessous pour plus de sélection de modèle:

7mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K
SE-705M			Resolution 640x480 , F/NO 2.8
SE-707M			LED 6 White LED bright light, Camera housing diameter Φ7mm
SE-710M			Wide visual view angle 62°
SE-715M			LED swith Adjustable lightness switch
SE-720M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g

5.5mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
E-USB2M			Camera 1/6" VGA COMS Pixel VGA 300K
E-USB5M			Resolution 640x480 , F/NO 2.8
E-USB7M			LED 6 White LED bright light, Camera housing diameter Φ5.5mm
E-USB10M			Wide visual view angle 62°
E-USB15M			LED swith Adjustable lightness switch
E-USB20M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g

14.5mm 4-LED USB Endoscope Camera

Item	Picture	Packing	Specification
EN-5M			Camera 1/6" VGA COMS Pixel VGA 300K
EN-10M			Resolution 640x480, F/NO 2.8
EN-15M			LED 6 White LED bright light, Camera housing diameter Φ14.5mm
EN-20M			Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 5M:230g 10M:410g 15M:560g 20M:710g

10mm 4-LED Endoscope Camera

Item	Picture	Packing	Specification
USB-2M			Camera 1/6" VGA COMS Pixel VGA 300K
USB-5M			Resolution 640x480, F/NO 2.8
USB-7M			LED 4 White LED bright light, Camera housing diameter Φ10mm
USB-10M			Wide visual view angle 62°
USB-15M			LED swith Adjustable lightness switch
USB-20M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g

Approval Certification:



Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

- 1.Established in 2005, about 10 years of history;
- 2.Own main factories, supply diversification products and One stop service
- 3.Certificates of ISO9001, UL, CE, EMC,CQC,RoHS,Reach,etc.
- 4.Six years Gold member in Alibaba, Aliexpress etc
- 5.Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!

