



### Product Features:

IP67 endoscope médical caméra de tube  
sauvegarder des fichiers vidéo, photo de votre PC  
Nous sommes fabricant d'origine  
Lumière 6LED réglable

### Principales Caractéristiques

- \* Imperméable endoscope fil
- \* Haute résolution avec caméra CMOS 1/6
- \* 6 lumières de luminance de lux faible LED peuvent travailler mieux quand la lumière est sombre
- \* Système de XP peut regarder la vidéo directement sans installer le logiciel, Vista ou Win7 doivent utiliser notre logiciel qui, dans le CD
- \* Peut prendre des photos et enregistrer sur votre PC
- \* Peut enregistrer de la vidéo, et enregistrer la vidéo sur votre PC
- \* Utilisé par automobile, moteur, mécaniques, de plomberie, de climatisation et d'autres la détection d'entretien
- \* Aider oeil à est difficile de voir et d'accès à l'emplacement

### Emballage:

1. Oculatif lentille waterpooof latéral x1
2. Couleur boîte x1
3. Les utilisateurs x1 manuel
4. CD x1
5. L'unité fil cam x1

### Product Pictures:



With waterpooof side lens





**Voir ci-dessous pour plus de sélection de modèle:**


### 7mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K <b>Resolution 640x480</b> , F/NO 2.8 LED 6 White LED bright light, <b>Camera housing diameter Φ7mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g
SE-705M			
SE-707M			
SE-710M			
SE-715M			
SE-720M			

### 5.5mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
E-USB2M			Camera 1/6" VGA COMS Pixel VGA 300K <b>Resolution 640x480</b> , F/NO 2.8 LED 6 White LED bright light, <b>Camera housing diameter Φ5.5mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g
E-USB5M			
E-USB7M			
E-USB10M			
E-USB15M			
E-USB20M			

### 14.5mm 4-LED USB Endoscope Camera

Item	Picture	Packing	Specification
EN-5M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 6 White LED bright light, <b>Camera housing diameter Φ14.5mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 5M:230g 10M:410g 15M:560g 20M:710g
EN-10M			
EN-15M			
EN-20M			

### 10mm 4-LED Endoscope Camera

Item	Picture	Packing	Specification
USB-2M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 4 White LED bright light, <b>Camera housing diameter Φ10mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g
USB-5M			
USB-7M			
USB-10M			
USB-15M			
USB-20M			

# Approval Certification:



## Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

- 1.Established in 2005, about 10 years of history;
- 2.Own main factories, supply diversification products and One stop service
- 3.Certificates of ISO9001, UL, CE, EMC,CQC,RoHS,Reach,etc.
- 4.Six years Gold member in Alibaba, Aliexpress etc
- 5.Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!

