



Product Features:

IP67 κάμερα σωλήνας ιατρική ενδοσκόπιο
αποθηκεύσετε το βίντεο, τη φωτογραφία στον υπολογιστή σας
Είμαστε αρχικό κατασκευαστή
6LED έντονο φως ρυθμιζόμενο

Βασικά Χαρακτηριστικά

- * Αδιάβροχο ενδοσκόπιο καλωδίων
- * Υψηλό ψήφισμα με τη 1/6 κάμερα CMOS
- * 6 LED χαμηλά φώτα φωτεινότητα lux μπορεί να λειτουργήσει καλύτερα όταν το φως είναι σκοτάδι
- * Το σύστημα XP μπορούν να παρακολουθήσουν βίντεο απευθείας χωρίς να εγκαταστήσετε το λογισμικό, Vista ή Win7 πρέπει να χρησιμοποιήσετε το λογισμικό μας που στο CD
- * Μπορεί να πάρει τη φωτογραφία και να το αποθηκεύσετε στον υπολογιστή σας
- * Μπορεί να καταγράψει βίντεο, και να αποθηκεύσετε το βίντεο στον υπολογιστή σας
- * Χρησιμοποιείται με αυτοκίνητο, μηχανή, μηχανική, υδραυλικές εγκαταστάσεις, κλιματισμό και άλλες ανίχνευσης συντήρησης
- * Assist ματιά είναι δύσκολο να δούμε και την πρόσβαση στην τοποθεσία

Συσκευασία:

1. Optional αδιάβροχους φακό πλευρά x1
2. Χρώμα κουτί x1
3. Οι χρήστες εγχειρίδιο x1
4. CD x1
5. Η μονάδα x1 έκκεντρο σύρμα

Product Pictures:



With waterpooof side lens





Δείτε παρακάτω για περισσότερες επιλογή μοντέλου:

7mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480 , F/NO 2.8 LED 6 White LED bright light, Camera housing diameter Φ7mm Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g
SE-705M			
SE-707M			
SE-710M			
SE-715M			
SE-720M			

5.5mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
E-USB2M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480 , F/NO 2.8 LED 6 White LED bright light, Camera housing diameter Φ5.5mm Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g
E-USB5M			
E-USB7M			
E-USB10M			
E-USB15M			
E-USB20M			

14.5mm 4-LED USB Endoscope Camera

Item	Picture	Packing	Specification
EN-5M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 6 White LED bright light, Camera housing diameter Φ14.5mm Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 5M:230g 10M:410g 15M:560g 20M:710g
EN-10M			
EN-15M			
EN-20M			

10mm 4-LED Endoscope Camera

Item	Picture	Packing	Specification
USB-2M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 4 White LED bright light, Camera housing diameter Φ10mm Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g
USB-5M			
USB-7M			
USB-10M			
USB-15M			
USB-20M			

Approval Certification:



Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

- 1.Established in 2005, about 10 years of history;
- 2.Own main factories, supply diversification products and One stop service
- 3.Certificates of ISO9001, UL, CE, EMC,CQC,RoHS,Reach,etc.
- 4.Six years Gold member in Alibaba, Aliexpress etc
- 5.Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!

