



### Product Features:

5 millimetri impermeabile fotocamera USB endoscopio  
 2M / 5M / 7M / 10M / 20M,  
 1 / macchina fotografica 6CMOS, 6LED luce  
 Nuovi prodotti di nuovo disegno.  
 Impermeabile: IP67

Plug & amp; Gioca senza installazione del driver sotto sistema XP  
 Installato automaticamente il software di cui sopra sytem XP quando si inserisce CD, in grado di salvare video, scattare foto, l'impostazione pixel video / formato / struttura / stile, etc  
 Alimentazione: DC 5V / 0.1A

Articoli di funzione	Spec Descrizione
Macchina fotografica	1/6 "COMS VGA
Pixel	640 X 480
Risoluzione	640x480,352X288,320X240,176X144,160X120
Captuer Risoluzione	Fino a 640X480
LED	Luce 4 LED bianco
Luminosità	Auto
Controllo a vista	Auto
F / NO	2.8
Camera diametro alloggiamento	Φ7.00 mm
Ampio angolo di visione visivo	62 °
Interruttore LED	Interruttore registrabile di leggerezza
Distanza focale	6CM-infinite

### I Nostri Servizi

1. superiore ed il migliore prezzo
2. Almeno 3 volte prova prima della consegna
3. garanzia di 24 mesi
4. trasporto più veloce
5. CE, ROHS approvato
6. L'ordine di prova è accolto favorevolmente
7. Termini di pagamento flessibili

### Product Pictures:





**Vedi sotto per più selezione del modello:**

### 7mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K <b>Resolution 640x480</b> , F/NO 2.8 LED 6 White LED bright light, <b>Camera housing diameter Φ7mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g
SE-705M			
SE-707M			
SE-710M			
SE-715M			
SE-720M			

### 5.5mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
E-USB2M			Camera 1/6" VGA COMS Pixel VGA 300K <b>Resolution 640x480</b> , F/NO 2.8 LED 6 White LED bright light, <b>Camera housing diameter Φ5.5mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g
E-USB5M			
E-USB7M			
E-USB10M			
E-USB15M			
E-USB20M			

### 14.5mm 4-LED USB Endoscope Camera

Item	Picture	Packing	Specification
EN-5M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 6 White LED bright light, <b>Camera housing diameter Φ14.5mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 5M:230g 10M:410g 15M:560g 20M:710g
EN-10M			
EN-15M			
EN-20M			

### 10mm 4-LED Endoscope Camera

Item	Picture	Packing	Specification
USB-2M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 4 White LED bright light, <b>Camera housing diameter Φ10mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g
USB-5M			
USB-7M			
USB-10M			
USB-15M			
USB-20M			

# Approval Certification:



## Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

- 1.Established in 2005, about 10 years of history;
- 2.Own main factories, supply diversification products and One stop service
- 3.Certificates of ISO9001, UL, CE, EMC,CQC,RoHS,Reach,etc.
- 4.Six years Gold member in Alibaba, Aliexpress etc
- 5.Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!

