

Product Features:

5 millimetri impermeabile fotocamera USB endoscopio 2M / 5M / 7M / 10M / 20M,

1 / macchina fotografica 6CMOS, 6LED luce

Nuovi prodotti di nuovo disegno.

Impermeabile: IP67

Plug & amp; Gioca senza installazione del driver sotto sistema XP

Installato automaticamente il software di cui sopra sytem XP quando si inserisce CD, in grado di salvare video, scattare foto, l'impostazione pixel video / formato / struttura / stile, etc

Alimentazione: DC 5V / 0.1A

Articoli di funzione	Spec Descrizione	
Macchina fotografica	1/6 "COMS VGA	
Pixel	640 X 480	
Risoluzione	640x480,352X288,320X240,176X144,160X120	
Captuer Risoluzione	Fino a 640X480	
LED	Luce 4 LED bianco	
Luminosità	Auto	
Controllo a vista	Auto	
F / NO	2.8	
Camera diametro alloggiamento	Φ7.00 mm	
Ampio angolo di visione visivo	62 °	
Interruttore LED	Interruttore registrabile di leggerezza	
Distanza focale	6CM-infinate	

I Nostri Servizi

- 1. superiore ed il migliore prezzo
- 2. Almeno 3 volte prova prima della consegna
- 3. garanzia di 24 mesi
- 4. trasporto più veloce
- 5. CE, ROHS approvato
- 6. L'ordine di prova è accolto favorevolmente
- 7. Termini di pagamento flessibili

Product Pictures:







Vedi sotto per più selezione del modello:

7mm 6-LED USB Endoscope Camera				
ltem	Picture	Packing	Specification	
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K	
SE-705M			Resolution 640x480, F/NO 2.8 LED 6 White LED bright light,	
SE-707M		0	Camera housing diameter Φ7mm Wide visual view angle 62°	
SE-710M	61809	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	LED swith Adjustable lightness switch Focal Distance 6CM-infinite	
SE-715M		O cost cost	I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual.	
SE-720M	_ /		G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g	
5.5mm 6-LED USB Endoscope Camera				
Item	Picture	Packing	Specification	
E-USB2M			Camera 1/6" VGA COMS	
E-USB5M		HD I SB F schoscopi Control Familia F	Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 6 White LED bright light,	
E-USB7M		- Service Control Cont	Camera housing diameter Φ5.5mm Wide visual view angle 62° LED swith Adjustable lightness switch	
E-USB10M		and the second s	Focal Distance 6CM-infinite I/O Interface USB 2.0	
E-USB15M			Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g	
E-USB20M				
14.5mm 4-LED USB Endoscope Camera				
Item	Picture	Packing	Specification	
EN-5M		WIRE CAM	Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 6 White LED bright light.	
EN-10M		WATER	Camera housing diameter Ф14.5mm Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite	
EN-15M		And the Landson	I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual.	
EN-20M			G.W: 5M:230g 10M:410g 15M:560g 20M:710g	
10mm 4-LED Endoscope Camera				
ltem	Picture	Packing	Specification	
USB-2M			Camera 1/6" VGA COMS	
USB-5M		To the Hand	Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 4 White LED bright light,	
USB-7M	200	C com	Camera housing diameter Φ10mm Wide visual view angle 62°	
USB-10M		Marian I.	LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0	
USB-15M		The state of the s	Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g	
USB-20M		Western Land	10M:390g 15M:550g 20M:680g	

Approval Certification:







Why Choose US:

Our goal is to provide customers products of high quality, competitive price, and superior services.

- 1.Established in 2005, about 10 years of history;
- 2.Own main factories, supply diversification products and One stop service
- 3. Certificates of ISO9001, UL, CE, EMC, CQC, RoHS, Reach, etc.
- 4. Six years Gold member in Alibaba, Aliexpress etc
- 5. Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8. We provide an excellent combination between prices, quality & respond, delivery, after-sales!

