



Product Features:

IP67 endoscopio medico fotocamera tubo
salvare i video, foto sul PC
Siamo produttore originale
Luce 6LED regolabile

Caratteristiche principali

- * Endoscopio filo impermeabile
- * Alta risoluzione con 1/6 CMOS
- * 6 luci luminanza lux basso LED possono funzionare meglio quando la luce è buio
- * Sistema di XP può guardare il video direttamente senza installare il software, Vista o Win7 bisogno usare il nostro software che nel CD
- * Può prendere la foto e salvarlo su PC
- * Può registrare il video, e salvare il video sul PC
- * Utilizzato in automobile, motore, meccanica, idraulica, climatizzazione e altri rilevazione di manutenzione
- * Assist interesse e 'difficile da vedere e accesso alla posizione

Confezione:

1. Oliente lato waterpooftional x1
2. Scatola di colore x1
3. Gli utenti x1 manuale
4. CD x1
5. La camma filo unità x1

Product Pictures:



With waterpooof side lens





Vedi sotto per più selezione del modello:

7mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480 , F/NO 2.8 LED 6 White LED bright light, Camera housing diameter Φ7mm Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g
SE-705M			
SE-707M			
SE-710M			
SE-715M			
SE-720M			

5.5mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
E-USB2M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480 , F/NO 2.8 LED 6 White LED bright light, Camera housing diameter Φ5.5mm Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g
E-USB5M			
E-USB7M			
E-USB10M			
E-USB15M			
E-USB20M			

14.5mm 4-LED USB Endoscope Camera

Item	Picture	Packing	Specification
EN-5M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 6 White LED bright light, Camera housing diameter Φ14.5mm Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 5M:230g 10M:410g 15M:560g 20M:710g
EN-10M			
EN-15M			
EN-20M			

10mm 4-LED Endoscope Camera

Item	Picture	Packing	Specification
USB-2M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 4 White LED bright light, Camera housing diameter Φ10mm Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g
USB-5M			
USB-7M			
USB-10M			
USB-15M			
USB-20M			

Approval Certification:

