

More models you can choose !



SE-MF

Product

Selectech

Selectech & 038; & 038;

Selectech HydroProbe

Selectech HydroProbe

Selectech

Selectech LED

& 038;

Supply Voltage	12-36V DC
Accuracy	0..100 RH
Resolution	0.1 RH
Power Consumption	0 5V DC 0 10V DC 4 20 RS485
Operating Temperature	+ -2 RH 10 95 RH 25 Celsius < + - 5 RH -40..80 Celsius
Storage Temperature	+ -0.3 RH
Relative Humidity	+ -0.3 RH
Resolution	0.1 RH
Accuracy	+ -0.5 RH
Material	DS18B20
Operating Temperature	25 Celsius + -0.3 Celsius
Power Consumption	0 5V DC 0 10V DC 4 20 RS485
Operating Temperature	0 50 Celsius -20 80 Celsius PCB
Storage Temperature	-40 60 Celsius
Accuracy	-40..80 Celsius
Material	ABS
Dimensions	Max 1.5mm ²

SE-MF



□□□□□

SE-MF3005□□□&□□□□□□□□5V DC; LED□□□□□□□□□□

SE-MF3105LED□□□&□□□□□□□□5V DC; LED□□□□□□□□□□□□

SE-MF3010□□□&□□□□□□□□10V DC; LED□□□□□□□□□□

SE-MF3110LED□□□&□□□□□□□□10V DC; LED□□□□□□□□□□□□

SE-MF3020□□□&□□□□□4□20□□□□□□□ LED□□□□□□□□□□

SE-MF3120LED□□□&□□□□□4□20□□□□□□□ LED□□□□□□□□□□□□

SE-MF3485□□□&□□□□RS485□□□ LED□□□□□□□□□□

SE-MF3485LED□□□&□□□□RS485□□□ LED□□□□□□□□□□□□

□□□□□



- 1. Established
- 2. Owns
- 3. Certificates
- 4. Six
- 5. Production 1000/
- 6. Monthly 50
- 7. Exported
- 8. We



send us inquiry



receive our quotation



negotiate details



mass production



sign contract / deposit



confirm the sample



cargo ready



balance / delivery



further cooperation

