□□□□□□□□□□□1A□□SE-MT148U 2□□USB□□□□Word□□□□□□

Product□□□□

1. AC□□□□6A 240VAC□□□□iPod□2TH□□□□□□□□□□□□□
2. USB□□□□□□□□□□□5VDC□□□□□□□□58□□□□
□□□□/□□□□□/□□□□□□□/□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□3□
1□□□□□□□□□4□□□□/□□/ EU / AU□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□□5.□
6. USB□□□□5V□□□□□□□10Ω□□□□□AC 100-250Vac□±5□□□□
7. USB□□□□□□□□□10Ω□□□□□□□□□□□□□□□□□□□□□4□□□450□1000□□□□□□□□□
8. USB□□□□□□□□5Ω□□□□□□□□□□□□□□□□□□□□□□□□□□□□□0.5hrs□□□□□
9. USB□□□□□□□□□□□□□□□□□□□□30secs□□□□□□□□□□□□□□□□□□□□□□
10.□□□□□□□□□□□□□□
11-WITH CHILDREN□□□□□□□
   -with 1□□□□□□□□□□□□□
   -with 100-240VAC VALTAGE□□
   -PATENT PROTECTED
   ABS 94V0□-PLASTIC CASES
12.Approval□FCC CE RoHS□□

□□ □□□

□□□□·□□□□

□□□□□**USB**□□□

SE-148U□USB□□5V□1000MA 1□□□

SE-148U-2.1A□USB□□5V□2100MA 1□□□

SE-148U2 USB□□5V□1000MA□□□□

SE-148U2-2.1A□USB□□5V□2100MA□□□□

ODM&□038; OEM□□□□□□□□□□□□□□□□□□□□□1Kpcs□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ect□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□

CTN QTY□100□/ CN

GW□12.00kgs

N.W□10.50□□□□□

□□□□40.5×31.5×30□□□□□□□

□□□□□

CQC

QUALITY MANAGEMENT SYSTEM

CERTIFICATE

Quality Management System

ISO9001: 2008

GB/T 19001-2008

CHINA QUALITY CERTIFICATION CENTRE

Union Safety Certification Service

EC Declaration of Conformity

EN60335-1:2012

EN62233:2008

Applicant

Address

Product : Humidity & temp Sensor

Model No.

Input Ratings

Ref. Test Report

CE

Manager

Union Safety Certification Service

Declaration of Compliance

Applicant

Address

Product : Humidity & temp Sensor

Model No.

Input Ratings

Ref. Test Report

RoHS

Signed and on behalf of

Union safety Certification Service

□□□□□□□□□□

2005□□□□□□□10□□□1.Established□
2.Owns□□□□□□□□□□□□□□□□□□□□□□□□□□□·□□□□·□□□□
ISO9001□UL□CE□SGS□EMC□CQC□□□□□□□3.Certificates
□□□□□Aliexpress□□□□4.Six□□□□□□□
5.Production□□100□□□□□□/□□
6.Monthly 50□□□□□□□□□□□□□□□□□
20□□□□□□□□7.Exported□
8.We□□□□□□□&□038□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□