

Support single channel or 4 channels display



<http://www.selectechcn.com>

Product Features:

1. 3.5" LCD screen, SD card slot, support single channel or 4 channels display. 2. 2.4GHz wireless transmission, 300m range. 3. 3.5" LCD screen, support single channel or 4 channels display. 4. 3.5" LCD screen, support single channel or 4 channels display.

2.4GHz wireless transmission, 300m range. 3. 3.5" LCD screen, support single channel or 4 channels display. 4. 3.5" LCD screen, support single channel or 4 channels display.

3.5" LCD screen, support single channel or 4 channels display. 300m range, 2.4G wireless transmission, 3.5" LCD screen, support single channel or 4 channels display.

* 3.5" LCD screen, support single channel or 4 channels display.

* 3.5" LCD screen, support single channel or 4 channels display.

* 3.5" LCD screen, support single channel or 4 channels display.

* 3.5" LCD screen, support single channel or 4 channels display.

* 3.5" LCD screen, support single channel or 4 channels display.

* 3.5" LCD screen, support single channel or 4 channels display.

* 3.5" LCD screen, support single channel or 4 channels display.

* 3.5" LCD screen, support single channel or 4 channels display.

* 雙 Dection 雙, 雙 雙雙 雙 雙 雙 雙雙 雙雙 雙雙.



* 2.4GHz 雙雙 雙 雙;

* 雙, 雙雙雙 雙雙 雙雙.

* 3.5 雙 雙雙雙雙 雙雙雙 LCD 雙雙雙雙, 雙雙 雙 雙;

* 雙雙 雙雙 雙雙 4 雙 雙雙雙雙;

* 雙雙 雙雙 雙 雙雙 雙雙雙雙雙 雙;

* 雙雙 64 雙 雙雙 SD 雙; 雙雙 雙雙 雙雙 雙;

* 雙雙 雙 Dection 雙, 雙雙 雙雙 雙雙雙 雙 雙 雙雙 雙, 雙雙 雙雙 雙雙雙 雙雙雙雙 雙雙 雙, 雙雙 雙雙 雙雙 雙;

* 9 雙 UI 雙雙 雙;

* 雙雙 雙雙 雙雙 UESD HD CMOS 雙雙 雙雙雙;

* 雙雙 雙雙 NTSC / PAL 雙雙 雙;

* 雙雙 雙雙雙雙 雙雙雙 雙雙 雙 / 雙雙 雙雙 USB 雙雙雙 雙雙 雙雙雙 雙雙 雙 雙雙;

* Infrared 雙, 雙雙 雙雙 雙雙 雙雙雙雙.

* 雙雙 雙雙 雙雙 雙雙 雙 (OSD);

* 雙雙 雙雙 雙雙雙 雙雙 雙, 雙雙 雙雙雙 雙雙 雙 雙 雙雙雙;



雙雙
雙雙 雙雙 雙
雙雙雙 雙雙
雙雙 雙雙
雙雙 雙雙
雙雙 雙雙
雙雙 雙雙 雙雙

雙雙

雙雙 雙雙
雙雙 雙雙
雙雙 雙雙 / 雙雙 雙雙
雙雙 雙雙
雙雙 雙雙
雙雙 雙雙
雙雙
雙雙雙 雙雙
雙雙 雙雙

雙雙 (雙雙)
640X480
NTSC / PAL
2400 MHz~2483MHz
3Mbps
DC 5V
1.5V 4 * AAA 雙雙 (雙雙 雙
雙 雙 雙雙)
'- (10)°C - 60°C
15 % ~ 85 % RH
1/4 CMOS
100 --- 300M
300mA (雙雙).
30 雙雙 / 雙
15 % ~ 85 % RH

LCD 雙雙
960X240
NTSC / PAL
2400 MHz~2483MHz
3Mbps
DC 5V
1100MA 4.2V 雙雙 雙雙
'- (10)°C - 60°C
15 % ~ 85 % RH
3.5"TFT-LCD
100 --- 300M
300mA (雙雙).
雙雙雙 64 雙雙 雙雙 雙雙
30 雙雙 / 雙
15 % ~ 85 % RH

Product Pictures:



<http://www.selectechcn.com>



<http://www.selectechcn.com>



□□ □□ :

, □□, □□□, □ □□ □□□□ □□ □□□ elderly.It □□ □□ □□□ □□, □□, □□□, □, □□□ □□□□ : □□□ □□ □□ □□□□□ □□ □□□ □□□□□.



Home



Hotel



Villa



Office

Product Packaging:

00 00 00
 1 0 00 000
 1 0 00 000 3.5 00 00
 00 000 000 (00 00 00 00 00 00) 0 00 1 X AC 000
 00 000 1 X AC 000 (00 00 00 00 00 00)
 LCD 000 1 X 1100MA 4.2V 00 000
 1 00 x 000 000 - 00
 00 00 : 0.48KG
 000 00 : 20X18.3X7.5CM



<http://www.selectechcn.com>

Approval Certification:





Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

1. Established in 2005, about 10 years of history;
2. Own main factories, supply diversification products and One stop service
3. Certificates of ISO9001, UL, CE, EMC, CQC, RoHS, Reach, etc.
4. Six years Gold member in Alibaba, Aliexpress etc
5. Production capability more than 100 thousands pcs/ month;
6. Monthly export more than 50 times delivery;
7. Exported to more than 20 countries and regions;
8. We provide an excellent combination between prices, quality & respond, delivery, after-sales!

Order program

Selectech



send us inquiry



receive our quotation



negotiate details



mass production



sign contract / deposit



confirm the sample



cargo ready



balance / delivery



further cooperation