



□□ □□□ □□ □□! □□□ □□□ □□ □□!

000000 00 00000 00000 00 0000 0000 0 00000 0000 00 000 0000000 000 00 0 000000.

Selectech LED, LED.

電源電圧	12-36V DC
湿度範囲	0..100 % RH
湿度精度	±0.3 % RH
温度範囲	0 ~ 5V DC 0 ~ 10V DC 4~20mA RS485
湿度精度	± 2 % RH (10~95% RH, 25Celsius); & LT + - 5 % RH (-40..80Celsius)
湿度精度	+ -0.3 % RH
湿度精度	+ -0.3 % RH
湿度精度	0.1 % RH
湿度精度	± 0.5 % RH
湿度精度	DS18B20
湿度精度	(25Celsius) + -0.3Celsius
湿度精度	0 ~ 5V DC 0 ~ 10V DC 4~20mA RS485
湿度精度	0 ~ 50Celsius -20 ~ 80Celsius, PCB 湿度センサー 湿度センサー 湿度センサー 湿度センサー
湿度精度	-40 ~ 60Celsius
湿度精度	-40..80Celsius
湿度精度	ABS
湿度精度	Max1.5mm ⁽²⁾

Page 10



<http://www.selectechcn.com>

□□□ □□ :

SE-MQ3005, □□ □ □□□ □□ 0 ~ 5V DC; LED □□□□□□ □□ □□,

SE-MQ3105LED, □□ □ □□□ □□ 0 ~ 5V DC; LED □□□□□□ □□ □□,

SE-MQ3010, □□ 0 ~ 10V DC □□ & A□ □□; LED □□□□□□ □□ □□,

SE-MQ3110LED, □□ 0 ~ 10V DC □□ & A□ □□; LED □□□□□□ □□ □□,

SE-MQ3020, □□ 4 ~ □□ & A□ □□ 20mA; LED □□□□□□ □□ □□,

SE-MQ3120LED, □□ 4 ~ □□ & A□ □□ 20mA; LED □□□□□□ □□ □□,

SE-MQ3485, □□ & A□□□ RS485 □□; LED □□□□□□ □□ □□,

SE-MQ3485LED, □□ & A□□□ RS485 □□; LED □□□□□□ □□ □□,

□□ □□ :



send us inquiry



receive our quotation



negotiate details



mass production



sign contract / deposit



confirm the sample



cargo ready



balance / delivery



further cooperation