



□□ □□□ □□ □□! □□□ □□□ □□ □□!

□□□□□□ □□ □□□□ □□□□ □□ □□□□ □□□□ □□ □□ □□□□□□ □□ □□ □□□□□□.

Selectech 公司 的 LED 燈泡 的 光 效 率 為 100lm/W, LED 燈 泡 的 光 效 率 為 100lm/W.

電源電圧	12-36V DC
湿度範囲	0..100 % RH
湿度精度	±0.3 % RH
温度範囲	0 ~ 5V DC 0 ~ 10V DC 4-20mA RS485
温度精度	± 2 % RH (10~95% RH, 25Celsius); & LT + - 5 % RH (-40..80Celsius)
湿度精度	+ -0.3 % RH
湿度精度	+ -0.3 % RH
湿度精度	0.1 % RH
湿度精度	± 0.5 % RH
湿度精度	DS18B20
湿度精度	(25Celsius) + -0.3Celsius
湿度精度	0 ~ 5V DC 0 ~ 10V DC 4-20mA RS485
湿度精度	0 ~ 50Celsius -20 ~ 80Celsius, PCB 湿度センサー 湿度センサー 湿度センサー 湿度センサー
湿度精度	-40 ~ 60Celsius
湿度精度	-40..80Celsius
湿度精度	ABS
湿度精度	Max1.5mm ⁽²⁾

Page 10



□□□ □□ :

SE-MQ3005, □□ □ □□□ □□ 0 ~ 5V DC□; LED □□□□□□ □□ □□,

SE-MQ3105LED, □□ □ □□□ □□ 0 ~ 5V DC□; LED □□□□□□ □□ □□,

SE-MQ3010, □□ 0 ~ 10V DC □□ & A□ □□; LED □□□□□□ □□ □□,

SE-MQ3110LED, □□ 0 ~ 10V DC □□ & A□ □□; LED □□□□□□ □□ □□,

SE-MQ3020, □□ 4 ~ □□ & A□ □□ 20mA; LED □□□□□□ □□ □□,

SE-MQ3120LED, □□ 4 ~ □□ & A□ □□ 20mA; LED □□□□□□ □□ □□,

00 00 :



10/10

2005 年 10 月 1. Established;
2. Owns 100% of the company;
ISO9001, UL, CE, SGS, EMC, CQC, 3. Certificates
4. Six years of experience
5. Production 100% on time;
6. Monthly 50,000 units;
20 years of experience 7. Exported;
8. We are a professional manufacturer; yes, we can!



send us inquiry



receive our quotation



negotiate details



mass production



sign contract / deposit



confirm the sample



cargo ready



balance / delivery



further cooperation