



More models you can choose !

**Product :**

Selectech sensors!

Selectech sensors are available in & A; and & A; models. The & A; model is a handheld device with a cable, and the & A; model is a multi-pin probe. The & A; model is a rectangular sensor with a cable, and the & A; model is a rectangular sensor with a cable. The & A; model is a probe with a metal tip, and the & A; model is a probe with a metal tip.

Selectech sensors are available in & A; and & A; models. The & A; model is a handheld device with a cable, and the & A; model is a multi-pin probe. The & A; model is a rectangular sensor with a cable, and the & A; model is a rectangular sensor with a cable. The & A; model is a probe with a metal tip, and the & A; model is a probe with a metal tip.

Selectech sensors are available in & A; and & A; models. The & A; model is a handheld device with a cable, and the & A; model is a multi-pin probe. The & A; model is a rectangular sensor with a cable, and the & A; model is a rectangular sensor with a cable. The & A; model is a probe with a metal tip, and the & A; model is a probe with a metal tip.

Selectech sensors are available in & A; and & A; models. The & A; model is a handheld device with a cable, and the & A; model is a multi-pin probe. The & A; model is a rectangular sensor with a cable, and the & A; model is a rectangular sensor with a cable. The & A; model is a probe with a metal tip, and the & A; model is a probe with a metal tip.

**& A; :**

Supply Voltage	12-36V DC
Humidity Range	0..100 % RH
Humidity Accuracy	± 2 % RH
Temperature Range	0 ~ 5V DC 0 ~ 10V DC 4-20mA RS485
Temperature Accuracy	± 2 % RH (10~95% RH, 25Celsius); & LT + - 5 % RH (-40..80Celsius)
Temperature Accuracy	+ -0.3 % RH
Temperature Accuracy	+ -0.3 % RH
Temperature Accuracy	0.1 % RH
Temperature Accuracy	± 0.5 % RH
Temperature Accuracy	DS18B20
Temperature Accuracy	(25Celsius) + -0.3Celsius
Temperature Accuracy	0 ~ 5V DC 0 ~ 10V DC 4-20mA RS485
Temperature Accuracy	0 ~ 50Celsius -20 ~ 80Celsius, PCB 4-20mA RS485
Temperature Accuracy	-40 ~ 60Celsius
Temperature Accuracy	-40..80Celsius
Temperature Accuracy	ABS
Temperature Accuracy	Max1.5mm <sup>(2)</sup>

**Product :**



□□□ □□ :

SE-MQ3005, □□ □ □□□ □□ 0 ~ 5V DC□; LED □□□□□□ □□ □□,  
SE-MQ3105LED, □□ □ □□□ □□ 0 ~ 5V DC□; LED □□□□□□ □□ □□,

SE-MQ3010, □□ 0 ~ 10V DC □□ & A□ □□; LED □□□□□□ □□ □□,  
SE-MQ3110LED, □□ 0 ~ 10V DC □□ & A□ □□; LED □□□□□□ □□ □□,

SE-MQ3020, □□ 4 ~ □□ & A□ □□ 20mA; LED □□□□□□ □□ □□,  
SE-MQ3120LED, □□ 4 ~ □□ & A□ □□ 20mA; LED □□□□□□ □□ □□,

SE-MQ3485, □□ & A□□□ RS485 □□; LED □□□□□□ □□ □□,  
SE-MQ3485LED, □□ & A□□□ RS485 □□; LED □□□□□□ □□ □□,

□□ □□ :



□ □□□ □□ :

- 2005 □□ □□□ □ 10 □□ 1.Established;
- 2.Owns □□ □□, □□ □□□ □ □ □ □□ □□□
- ISO9001, UL, CE, SGS, EMC, CQC, □□ □□ 3.Certificates
- □□□□, Aliexpress□ 4.Six □ □□ □□
- 5.Production □□ 100 □ □□□ □□ □ / □;
- 6.Monthly 50 □□ □□□ □□;
- 20 □ □□□ □□ □□□ 7.Exported;
- 8.We □□ □□, □□ □ A □□□ □□□ □□□ □□□□; □□, □□, □□ □!



send us inquiry



receive our quotation



negotiate details



mass production



sign contract / deposit



confirm the sample



cargo ready



balance / delivery



further cooperation

