

Travel worldwide with travel adapter



USB 1A SE-MT148U 2

Product :

1. AC Max 6A 240VAC 2 ports
2. USB Max 1,000mA 5VDC, 58 %
3. 1 / 2 / 3 / 4 / AU ports
4. 1 / 2 / 3 / 4 / AU ports
5. 5.0V
6. USB Max 1,000mA $\pm 5\%$ 10 Ω AC 100-250VAC 5V
7. 10 Ω USB Max 450~1,000mA 4 ports
8. USB Max 5V 1,000mA 0.5hrs
9. USB Max 5V 1,000mA 30 ports
10. : ,
- (11) - ABS 94V0 CASES
12. Approval : FCC CE RoHS

Image :



<http://www.selectechcn.com>



<http://www.selectechcn.com>

□□ □□ :

□□ □□ □□ **USB** □□

SE-148U□ USB □□ 5V, 1000MA □□□ □□

SE-148U-2.1A□ USB □□ 5V, 2100MA □□□ □□

SE-148U2□ USB □□ 5V, 1000MA □ □□

SE-148U2-2.1A□ USB □□ 5V, 2100MA □ □□

ODM & A, OEM□ □□□ MOQ□ □□ □□□□□ : 1Kpcs □□. □□□ □□□ □□□ □□ □ □ □□□□, □□ □□□□□□. □□□ □□□ □□□□ □□□ □□ □□ □□□□□! □□□ □□ □□□ □□ □□□!

□□ □□ :

CTN □□ : 100PCS / CN

GW : 12.00kgs

N.W : 10.50 □□□□

□□ : 40.5 × 31.5 × 30cm

□□ □□ :



