

Features:

- 1. Shell is made of high quality fire retardant PC material, up to the European environmental requirements, burning non-toxic.
- 2.Inside Material is made of Tin phosphorous bronze, with good electrical conductivity, not easily deformed.
- 3.Built-in automatic recovery fuse, more safe.
- 4. Automatically adjust charging Wattage.
- 5.USB charging and Type C interface, support more USB devices and mobile phone to charging at the same time.
- 6.2100 mA or 4000mA output current, can reduce charging time.
- 7.Compatibility: iPod, iPhone, iPad, Tablets, Mobile Phones, MP3 Bluetooth Headsets, GPS & more.



Product Description:

- · Type: Wall Socket
- · Grounding: Standard Grounding
- · Application: Residential / General-Purpose
- · Main material: High quality PC Material
- · Inside Material: Tin phosphorous bronze
- · Electrical Characteristics: AC125V /20A
- · USB output: DC 5.0V /2100mA/4000mA
- · Color: White or Black
- · Insert and Draw Frequency: >10000 times
- · Socket standard: Multi function socket
- · Certificate: CE,ROHS,TUV,ETL Certificate
- · Pressure Ressistance: Between the input output 3KV / AC
- · Isolation Ressistance: Input and output 500VDC / $100M\Omega$

· Color: White

· Product size: 115 x 70 mm

· Insert and Draw Frequency>10000 times

· Temperature, humidity:-10°C \sim +40°C ; 20% \sim 90%

· Storage Temperature, Humidity: -20°C \sim +85°C ; 10% \sim 95% RH



Packaging & Shipping

· Packaging: 1PCS/Poly bag/Inner box / 50PCS/Carton

· Carton size: 40*26*30cm

Or as customized.



Our Advantages:

- 1.We can print your logo on products according to your requirements.
- 2. We can supply these products with spray painting.
- 3. We can manufacture these products on any color that you requested on the basis of your quantity.
- 4. We can manufacture your customized package.
- 5. Good quality with competitive price, different colors and sizes are available.

More embedded Inner core:







USB output voltage: DC 5.0V USB output current: 2.1A USB:TYPE A+TYPE A Color: White

(2)

XJY-USB-31-A/A

AC input parameters: AC125V USB output voltage: DC 5.0V USB output current: 2.1A USB:TYPE A+TYPE A

Color: White





(3)

XJY-USB-30-A/C

AC input parameters: AC125V USB output voltage: DC 5.0V USB output current: 2.1A USB: TYPE A+TYPE C Color: White

4

XJY-USB-31-A/C

AC input parameters: AC125V USB output voltage: DC 5.0V USB output current: 2.1A USB:TYPE A+TYPE C

Color: White

The Best Wall Outlets With USB Charging Ports





USB Wall Outlet Charger Factory

