

180 Degree Krone-110 DUAL modular Cat 3 RJ11 Keystone Jack

The Keystone Jack is designed to easily snap in and out of the wall outlet, patch panel and surface mount box. With special design insulation displacement connectors (IDC), the LAN wires can be terminated without punchdown tool for quick installation.

It comes with T568A/T568B color label and fully complies with ANSI/TIA-568-C.2-2009 specifications.

Products Features:

1. Lead-free & RoHS compliant.
2. Meet the ANSI/TIA-568-C.2, ISO/IEC 11801 2nd edition and CENELEC EN 50173-1 cabling requirements for Category 6 channel performance.
3. Comply with requirements of ANSI/TIA-1096-A (FCC Part 68) and reliability requirements of IEC 60603-7 for RJ45 8-way connector.

Specifications:

Meet TIA/EIA-568-A and TIA/EIA-568-B Category 6 requirements.

Meet TIA/EIA TSB-40

Meet ISO/IEC Generic Cabling Standard 11801

Meet CENELEC Generic Cabling Standard EN50173

Angle: 180 Degree

Termination: Krone- 110- DUAL Type

Electrical:

According to UL 1863

Current rating: 1.5 Amp Max.

Voltage rating: 150 Volts

Contact resistance: 20 m-ohm

Insulation Resistance: 500M-ohm

Dielectric Withstand Voltage: 1000 V AC RMS, 60Hz 1min

Materials:

Housing: PC UL94V-0

IDC: PC UL94V-0, Accept 22-26 AWG Solid Wire.

PCB: FR4 1.6mm(0.04") thickness, 2 layers

Contact: PC UL94V-0, 0.45mm(0.018") Diameter Phosphor bronze with 3 U" to 50 U"

Gold plating on contact area.

