

American Style Decor Duplex easy to install USB wall socket plate cover with dual high speed USB charger ports for home use and business office use





Rated voltage	100-240V	Current Rating	15A /20A
Creepage distance	$\geq 3\text{mm}$	CLEARANCE	$\geq 3\text{mm}$
Conductor material	Phosphor Bronze	Housing Material	PC fire-retardant
Mechanical life	≥ 5000 times (USB plugs and receptacles not exceeding 10mm / sec mating frequency of less than 12 beats / min)	DC output voltage	DC 5V
Output voltage tolerance	$\pm 3\%$	Output current	0~2100mA/4000mA
DC output power	10.5W max	power	78%
No-load power consumption	0.2W max	Input voltage	100 - 240V/AC 50~60Hz
Housing Material	PC fire-retardant	Temperature, humidity	$-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$ 20% ~ 90% RH
Storage Temperature, Humidity	$-20^{\circ}\text{C} \sim +85^{\circ}\text{C}$ 10% ~ 95% RH	Pressure resistance	Between the input output 3KV / AC
Isolation resistance	Input and output 500VDC / 100M Ω	Carton size	40*26*30cm
Qty	1Pcs / box; 50Pcs / box		

USB Wall Socket

120 American Standard Series

XJY-USB-37-5V/3.1A

XJY-USB-37B-5V/3.1A

XJY-USB-37C-5V/2.1A

XJY-USB-37D-5V/2.1A



1 Turn power off to outlet and remove cover plate.



2 Insert Charger over outlet.



3 Screw on the screws



Model	XJY-USB-37	XJY-USB-37B	XJY-USB-37C	XJY-USB-37D
Size	70×160			
USB output current	5V/3.1A		5V/2.1A	
AC input parameters	AC125V 50-60Hz			
Colour	White/Black			

More Products you [Contact Us.](#)