



## Digital humidity and temperature sensor Model:SE-RHT03

### Product Features:

RHT03 output calibrated digital signal. It utilizes exclusive digital-signal-collecting-technique and humidity sensing technology, assuring its reliability and stability. Its sensing elements is connected with 8-bit single-chip computer.

Every sensor of this model is temperature compensated and calibrated in accurate calibration chamber and the calibration-coefficient is saved in type of programme in OTP memory, when the sensor is detecting, it will cite coefficient from memory.

Small size & low consumption & long transmission distance(20m) enable RHT03 to be suited in all kinds of harsh application occasions.

### Specs&Description:

Power supply:	3.3-5V DC
Output signal:	digital signal via single-bus
Operating range:	humidity 0-100%RH, temperature -40~80Celsius
Accuracy:	humidity $\pm 2\%RH$ (Max $\pm 5\%RH$ ), temperature $\pm 0.5Celsius$
Resolution:	humidity 0.1%RH, temperature 0.1Celsius
Repeatability:	humidity $\pm 1\%RH$ , temperature $\pm 0.5Celsius$
Response time:	Average:5s
Humidity hysteresis:	$\pm 0.5\%RH$
Stability:	$\pm 0.5\%RH/Year$
Interchangeability:	fully interchangeable
Dimensions:	22*28*5mm

### Product Pictures:



## Approval Certification:



## Why Choose US :

- 1.Established in 2005, about 10 years of history;
- 2.Owns main factories, supply diversification products and One stop service service
- 3.Certificates of ISO9001, UL, CE, SGS,EMC,CQC,Reach,etc
- 4.Six years Gold member in Alibaba, Aliexpress etc
- 5.Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!

## Order program

Selectech

