



### Product Features:

5 milímetros à prova d'água câmera usb endoscópio  
 2M / 5M / 7M / 10M / 20M,  
 1 / câmera 6CMOS, 6LED luz  
 Novos produtos novo design.  
 Waterproof: IP67

Plug & amp; Jogar sem instalação de driver abaixo sistema XP  
 Automaticamente instalado o software acima do sytem XP quando você inserir o CD, é possível salvar vídeo, toma a foto, definição de vídeo pixels / tamanho / frame / estilo, etc  
 Fonte de alimentação: DC 5V / 0.1A

Itens de função	Spec Descrição
Câmera	1/6 "VGA COMS
Pixel	640 X 480
Resolução	640x480,352X288,320X240,176X144,160X120
Resolução Captuer	Até 640X480
LED	4 LED de luz branca brilhante
Brilho	Automático
Controle exposto	Automático
F / NO	2.8
Diâmetro caixa da câmera	Φ7.00 mm
Ângulo de visão visual largo	62 °
Interruptor de LED	Interruptor leveza ajustável
Distância focal	6CM-infinite

### Nossos Serviços

1. A qualidade superior eo melhor preço
2. Pelo menos 3 vezes testar antes do parto
3. garantia de 24 meses
4. transporte mais rápido
5. CE, ROHS aprovado
6. A ordem experimental é bem-vinda
7. condições de pagamento flexíveis

### Product Pictures:





**Veja abaixo para mais selecções modelo:**

### 7mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K <b>Resolution 640x480</b> , F/NO 2.8 LED 6 White LED bright light, <b>Camera housing diameter Φ7mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g
SE-705M			
SE-707M			
SE-710M			
SE-715M			
SE-720M			

### 5.5mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
E-USB2M			Camera 1/6" VGA COMS Pixel VGA 300K <b>Resolution 640x480</b> , F/NO 2.8 LED 6 White LED bright light, <b>Camera housing diameter Φ5.5mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g
E-USB5M			
E-USB7M			
E-USB10M			
E-USB15M			
E-USB20M			

### 14.5mm 4-LED USB Endoscope Camera

Item	Picture	Packing	Specification
EN-5M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 6 White LED bright light, <b>Camera housing diameter Φ14.5mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 5M:230g 10M:410g 15M:560g 20M:710g
EN-10M			
EN-15M			
EN-20M			

### 10mm 4-LED Endoscope Camera

Item	Picture	Packing	Specification
USB-2M			Camera 1/6" VGA COMS Pixel VGA 300K Resolution 640x480, F/NO 2.8 LED 4 White LED bright light, <b>Camera housing diameter Φ10mm</b> Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g
USB-5M			
USB-7M			
USB-10M			
USB-15M			
USB-20M			

# Approval Certification:





## Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

- 1.Established in 2005, about 10 years of history;
- 2.Own main factories, supply diversification products and One stop service
- 3.Certificates of ISO9001, UL, CE, EMC,CQC,RoHS,Reach,etc.
- 4.Six years Gold member in Alibaba, Aliexpress etc
- 5.Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!

