



Product Features:

IP67 câmera tubo de endoscópio médico
salvar o vídeo, foto em seu PC
Nós somos fabricante original
Luz brilhante 6LED ajustável

Características Principais

- * Endoscópio fio à prova d'água
- * Alta resolução com 1/6 câmera CMOS
- * 6 de baixo lux de luminância luzes LED pode funcionar melhor quando a luz é escuro
- * Sistema XP pode assistir a vídeos diretamente, sem instalar o software, o Vista ou Win7 precisa usar nosso software que no CD
- * Pode tirar foto e salvá-lo em seu PC
- * Pode gravar vídeo e salvar o vídeo em seu PC
- * Usado por automóvel, motor, mecânica, canalização, ar condicionado e outros detecção de manutenção
- * Assist olhada é difícil ver e acesso ao local

Embalagem:

1. Olente lado waterpoof ptional x1
2. Caixa de cor x1
3. Os usuários X1 manual
- X1 4. CD
- 5.A unidade de fio de came x1

Product Pictures:



With waterpooof side lens





Veja abaixo para mais selecções modelo:

7mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K
SE-705M			Resolution 640x480 , F/NO 2.8
SE-707M			LED 6 White LED bright light, Camera housing diameter Φ7mm
SE-710M			Wide visual view angle 62°
SE-715M			LED swith Adjustable lightness switch
SE-720M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g

5.5mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
E-USB2M			Camera 1/6" VGA COMS Pixel VGA 300K
E-USB5M			Resolution 640x480 , F/NO 2.8
E-USB7M			LED 6 White LED bright light, Camera housing diameter Φ5.5mm
E-USB10M			Wide visual view angle 62°
E-USB15M			LED swith Adjustable lightness switch
E-USB20M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g

14.5mm 4-LED USB Endoscope Camera

Item	Picture	Packing	Specification
EN-5M			Camera 1/6" VGA COMS Pixel VGA 300K
EN-10M			Resolution 640x480, F/NO 2.8
EN-15M			LED 6 White LED bright light, Camera housing diameter Φ14.5mm
EN-20M			Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 5M:230g 10M:410g 15M:560g 20M:710g

10mm 4-LED Endoscope Camera

Item	Picture	Packing	Specification
USB-2M			Camera 1/6" VGA COMS Pixel VGA 300K
USB-5M			Resolution 640x480, F/NO 2.8
USB-7M			LED 4 White LED bright light, Camera housing diameter Φ10mm
USB-10M			Wide visual view angle 62°
USB-15M			LED swith Adjustable lightness switch
USB-20M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g

Approval Certification:



Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

- 1.Established in 2005, about 10 years of history;
- 2.Own main factories, supply diversification products and One stop service
- 3.Certificates of ISO9001, UL, CE, EMC,CQC,RoHS,Reach,etc.
- 4.Six years Gold member in Alibaba, Aliexpress etc
- 5.Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!

