

### Product Features:

водонепроницаемый 5 мм USB эндоскоп камеры  
 2М / 5М / 7М / 10М / 20М,  
 1 / 6СМOS камера, свет 6LED  
 Новые товары новый дизайн.  
 Водонепроницаемость: IP67

Правда Подключите & AMP; Играть без установки драйвера ниже системы XP  
 Автоматически установлен над системном XP, когда вы вставляете диск, может спасти видео,  
 сфотографировать, установка видео пикселей / размера / рамки / стиль, и т.д. программное  
 обеспечение

Питание: DC 5V / 0.1A

Функциональные элементы	Спец Описание
Камера	1/6 "VGA COMS
Пиксель	640 X 480
Разрешение	640x480,352X288,320X240,176X144,160X120
Сартuer Разрешение	До 640X480
СВЕТОДИОД	4 Белый светодиод яркий свет
Яркость	Автоматический
Выставленный управления	Автоматический
Ж / НЕТ	2.8
Камера диаметр корпуса	Ф7.00 мм
Широкий угол зрения зрения	62 °
Переключатель СИД	Регулируемый переключатель легкость
Фокусное расстояние	6CM-infinite

### Наши Услуги

1. Высокое качество и самое лучшее цена
2. По крайней мере, 3 раза тест до доставки
3. 24 месяцев гарантии
4. быстрая перевозка груза
5. CE, ROHS утвержден
6. Пробный заказ приветствуется
7. Гибкие условия оплаты

### Product Pictures:





**Ниже более модели выбора:**


### 7mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
SE-702M			Camera 1/6" VGA COMS Pixel VGA 300K
SE-705M			<b>Resolution 640x480</b> , F/NO 2.8
SE-707M			LED 6 White LED bright light, <b>Camera housing diameter Φ7mm</b>
SE-710M			Wide visual view angle 62°
SE-715M			LED swith Adjustable lightness switch
SE-720M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:120g 5M:220g 7M:280g 10M:400g 15M:550g 20M:680g

### 5.5mm 6-LED USB Endoscope Camera

Item	Picture	Packing	Specification
E-USB2M			Camera 1/6" VGA COMS Pixel VGA 300K
E-USB5M			<b>Resolution 640x480</b> , F/NO 2.8
E-USB7M			LED 6 White LED bright light, <b>Camera housing diameter Φ5.5mm</b>
E-USB10M			Wide visual view angle 62°
E-USB15M			LED swith Adjustable lightness switch
E-USB20M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, G.W: 2M:100g 5M:200g 7M:250g 10M:380g 15M:540g 20M:670g

### 14.5mm 4-LED USB Endoscope Camera

Item	Picture	Packing	Specification
EN-5M			Camera 1/6" VGA COMS Pixel VGA 300K
EN-10M			Resolution 640x480, F/NO 2.8
EN-15M			LED 6 White LED bright light, <b>Camera housing diameter Φ14.5mm</b>
EN-20M			Wide visual view angle 62° LED swith Adjustable lightness switch Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 5M:230g 10M:410g 15M:560g 20M:710g

### 10mm 4-LED Endoscope Camera

Item	Picture	Packing	Specification
USB-2M			Camera 1/6" VGA COMS Pixel VGA 300K
USB-5M			Resolution 640x480, F/NO 2.8
USB-7M			LED 4 White LED bright light, <b>Camera housing diameter Φ10mm</b>
USB-10M			Wide visual view angle 62°
USB-15M			LED swith Adjustable lightness switch
USB-20M			Focal Distance 6CM-infinite I/O Interface USB 2.0 Packing details: endoscope camera, CD, manual. G.W: 2M:110g 5M:210g 7M:260g 10M:390g 15M:550g 20M:680g

# Approval Certification:



## Why Choose US :

Our goal is to provide customers products of high quality, competitive price, and superior services.

- 1.Established in 2005, about 10 years of history;
- 2.Own main factories, supply diversification products and One stop service
- 3.Certificates of ISO9001, UL, CE, EMC,CQC,RoHS,Reach,etc.
- 4.Six years Gold member in Alibaba, Aliexpress etc
- 5.Production capability more than 100 thousands pcs/ month;
- 6.Monthly export more than 50 times delivery;
- 7.Exported to more than 20 countries and regions;
- 8.We provide an excellent combination between prices, quality & respond,delivery,after-sales!

